


UNITEx™ -D

CAPTIVE COMPONENT GLAND® WITH VARIABLE DELUGE SEAL™ for Multi Armoured Cable



Features and Benefits

- Gland for use in ordinary and hazardous locations.
- Two part handling, no loose parts.
- Freely rotating captive cone and inspectible cone ring provides an armour clamp and earth bond on steel wire, aluminium, braid and tape armour.
- Patented disconnect system that allows inspection of armour clamp and inner seal after assembly.
- With a patented Variable Deluge Seal™ as standard.
- Factory fitted with a specially formulated elastomeric seal for Built-in Safety™, seals on the inner and outer sheath of the cable to IP65/66/68.
- Precision manufactured from high-quality brass (Marine Grade Electroless Nickel Plated™) available in aluminium and stainless steel 316/316L on request.
- Supplied with a thread-sealing gasket (parallel threads only).



Technical Data


Type:	UNITEx™-D
Gland Material:	Brass (Marine Grade Electroless Nickel Plated™), Aluminium, Stainless Steel 316/316L
Seal Material:	Standard Thermoset Elastomer or Extreme Temperature Seals
Sealing Gasket Material:	HDPE, Nylon 66 or PTFE
Cable Type:	Steel or Aluminium wire, Braided or Tape Armour
Armour Clamping:	Rotating Captive Cone and Inspectible Cone Ring
Sealing Area:	Inner Sheath, Outer Sheath and Variable Deluge Seal™
Optional Accessories:	Adaptor, Reducer, Earth Tag, Locknut, Serrated Washer and Shroud
Note:	The installer should ensure that the materials are suitable for the installation environment.

Temperature Range

When fitted with sealing gaskets the temperature range for the gland will be:-
 Sealing Gasket Material: Standard Seals: -60°C and +95°C/100°C(HDPE/Nylon Sealing Gasket)
 Extreme Temp. Seals: -60°C and +160°C (PTFE Sealing Gasket)

Standards and Certifications

Equipment Protection Levels:	NEC / CEC: CI I Div 2 Gr ABCD, CI II Div 2 Gr FG, CI III Div 2 Ex db IIC Gb, CI I Zn 1AEx eb IIC Gb / Ex eb IIC Gb Zn 20 AEx ta IIIC Da / Ex ta IIIC Da, CI I Zn 2 AEx nR IIC Gc / Ex nR IIC Gc, IP66/67/68, IP65, Type 4X	
	IECEX: Ex db IIC Gb, Ex eb IIC Gb, Ex ta IIIC Da, Ex nR IIC Gc	
Conformance:	Standard:	Certificate:
CEC	CSA C22.2 No. 18.3-12, 174:2018 & 213:2017	E115595
	CSA C22.2 No. 60079 - 0, 1, 7, 15, 31	
NEC	UL514B, UL121201 UL 60079 - 0, 7, 15, 31	
IECEX	IEC 60079 - 0, 1, 7, 15, 31	IECEX CML 18.0018X
IP66/68 850m – Parallel	IEC 60529	CML 15Y728
IP68 – Tapered and approved grease	IEC 60529	IECEX CML 18.0018X
Nema Type 4X	NEMA 250	E115595
Deluge Protection	DTS-01	CML 14CA370-2
Corrosion Protection	ASTM B117-11, BS EN ISO 3231	EXOVA N968667
Marine ABS	IEC/EN 60079 - 0, 1, 7, 15, 31	ABS 20-SG1952706-PDA
DNV	IEC 60079 - 0, 1, 7, 31, IEC 60529	TAE0000010
ClassNK	IEC 60079 - 0, 1, 7, 31, IEC 60529	TA20270M
EMC Compatible	EN 55011, + A1, EN 55022	SGS EMC305079/1



Installation Requirements / Specific Conditions of Use

- The cable glands, sizes M20, ¾" NPT and smaller, shall only be used on fixed installations where the cable is clamped, or stress applied to the cable in the gland is prevented. (NEC/CEC only)
- The cable glands, when supplied with suffix 'FC', shall only be used with an approved UL 514B conduit fitting. (NEC/CEC only)
- Braided cables must only be used on fixed installations where the cable is clamped or stress applied to the gland is prevented. (IECEX only)
- The cable glands shall only be used if the temperature, at the point of entry, is as specified above.

NPT Entry Thread

Gland Size Ref	Product Code	NPT Entry Thread		Alternative Thread Product Code	NPT Entry Thread		Cable Detail				Max Length 'E'	Armour Dia		Hexagonal Detail	
		'C'	Min 'D'		'C'	Min 'D'	Min 'A'	Max 'A'	Min 'B'	Max 'B'		Min 'F'	Max 'F'	Max 'Flats'	Max 'Crns'
00-20ss	055400-012NPT-MNA	½	0.590	055400-034NPT-MNA	¾	0.590	0.118	0.335	0.315	0.531	2.204	0.008	0.035	0.945	1.063
0-20s	0554-0-012NPT-MNA	½	0.590	0554-0-034NPT-MNA	¾	0.590	0.275	0.472	0.453	0.630	2.322	0.008	0.049	0.945	1.063
1-20	055401-012NPT-MNA	½	0.590	055401-034NPT-MNA	¾	0.590	0.354	0.590	0.571	0.807	2.873	0.008	0.049	1.063	1.181
2s-25s	055422-034NPT-MNA	¾	0.590	055422-001NPT-MNA	1	0.748	0.433	0.689	0.630	0.965	3.227	0.008	0.063	1.377	1.535
2-25	055402-034NPT-MNA	¾	0.590	055402-001NPT-MNA	1	0.748	0.551	0.787	0.807	1.043	3.227	0.008	0.063	1.377	1.535
3s-32s	055433-001NPT-MNA	1	0.748	055433-114NPT-MNA	1¼	0.748	0.590	0.866	0.906	1.200	3.699	0.008	0.079	1.653	1.850
3-32	055403-001NPT-MNA	1	0.748	055403-114NPT-MNA	1¼	0.748	0.748	1.043	1.039	1.319	3.699	0.008	0.079	1.653	1.850
4s-40s	055444-114NPT-MNA	1¼	0.748	055444-112NPT-MNA	1½	0.826	0.866	1.240	1.181	1.555	3.935	0.012	0.079	2.046	2.322
4-40	055404-114NPT-MNA	1¼	0.748	055404-112NPT-MNA	1½	0.826	1.023	1.338	1.299	1.673	4.132	0.012	0.079	2.046	2.322
5s-50s	055455-112NPT-MNA	1½	0.826	055455-002NPT-MNA	2	0.826	1.141	1.495	1.339	1.870	4.762	0.016	0.098	2.558	2.873
5-50	055405-112NPT-MNA	1½	0.826	055405-002NPT-MNA	2	0.826	1.338	1.751	1.673	2.063	4.762	0.016	0.098	2.558	2.873
6s-63s	055466-002NPT-MNA	2	0.826	055466-212NPT-MNA	2½	1.181	1.495	1.968	1.791	2.381	4.959	0.016	0.098	3.148	3.542
6-63	055406-002NPT-MNA	2	0.826	055406-212NPT-MNA	2½	1.181	1.732	2.224	2.067	2.579	4.959	0.016	0.098	3.148	3.542
7s-75s	055477-212NPT-MNA	2½	1.181	055477-003NPT-MNA	3	1.259	1.968	2.440	2.244	2.854	5.431	0.016	0.124	3.778	4.250
7-75	055407-212NPT-MNA	2½	1.181	055407-003NPT-MNA	3	1.259	2.204	2.656	2.579	3.070	5.431	0.016	0.124	3.778	4.250
8-80	055408-003NPT-MNA	3	1.259	-	-	-	2.322	2.715	2.560	3.051	5.588	0.016	0.124	3.778	4.250
9s-90s	055499-003NPT-MNA	3	1.259	055499-312NPT-MNA	3½	1.299	2.597	2.952	2.874	3.406	6.139	0.016	0.138	4.368	4.919
9-90	055409-003NPT-MNA	3	1.259	055409-312NPT-MNA	3½	1.299	2.912	3.207	3.227	3.581	6.139	0.016	0.138	4.368	4.919
10-10	055410-312NPT-MNA	3½	1.299	055410-004NPT-MNA	4	1.338	3.188	3.581	3.542	3.935	6.808	0.016	0.138	4.919	5.549

All dimensions are in inches. Intermediate thread sizes are available on request. NPT threads should be tightened 'wrench tight'

CCG reserves the right to make alterations to the technical data, dimensions, designs and products available without notice. The illustrations cannot be considered binding. Please contact CCG for assistance. UNITEX_D-OMG260724NA

Metric Entry Thread

Gland Size Ref	Product Code	Metric Entry Thread		Cable Detail				Max Length 'E'	Armour Dia		Hexagonal Detail		Tightening Torque Nm/lb ft
		'C'	Min 'D'	Min 'A'	Max 'A'	Min 'B'	Max 'B'		Min 'F'	Max 'F'	Max 'Flats'	Max 'Crms'	
00-20ss	055400-MNA	M20x1.5	0.591	0.118	0.335	0.315	0.531	2.205	0.008	0.035	0.945	1.063	21/15
0-20s	0554-0-MNA	M20x1.5	0.591	0.276	0.472	0.453	0.630	2.323	0.008	0.049	0.945	1.063	21/15
1-20	055401-MNA	M20x1.5	0.591	0.354	0.591	0.571	0.807	2.874	0.008	0.049	1.063	1.181	21/15
2s-25s	055422-MNA	M25x1.5	0.591	0.433	0.689	0.630	0.965	3.228	0.008	0.063	1.378	1.535	30/22
2-25	055402-MNA	M25x1.5	0.591	0.551	0.787	0.807	1.043	3.228	0.008	0.063	1.378	1.535	30/22
3s-32s	055433-MNA	M32x1.5	0.591	0.591	0.866	0.906	1.200	3.701	0.008	0.079	1.654	1.850	42/31
3-32	055403-MNA	M32x1.5	0.591	0.748	1.043	1.039	1.319	3.701	0.008	0.079	1.654	1.850	42/31
4s-40s	055444-MNA	M40x1.5	0.591	0.866	1.240	1.181	1.555	3.937	0.012	0.079	2.047	2.323	52/38
4-40	055404-MNA	M40x1.5	0.591	1.024	1.339	1.299	1.673	4.134	0.012	0.079	2.047	2.323	52/38
5s-50s	055455-MNA	M50x1.5	0.591	1.142	1.496	1.339	1.870	4.764	0.016	0.098	2.559	2.874	57/42
5-50	055405-MNA	M50x1.5	0.591	1.339	1.752	1.673	2.063	4.764	0.016	0.098	2.559	2.874	57/42
6s-63s	055466-MNA	M63x1.5	0.591	1.496	1.969	1.791	2.381	4.961	0.016	0.098	3.150	3.543	66/49
6-63	055406-MNA	M63x1.5	0.591	1.732	2.224	2.067	2.579	4.961	0.016	0.098	3.150	3.543	66/49
7s-75s	055477-MNA	M75x1.5	0.591	1.969	2.441	2.244	2.854	5.433	0.016	0.124	3.780	4.252	72/53
7-75	055407-MNA	M75x1.5	0.591	2.205	2.657	2.579	3.070	5.433	0.016	0.124	3.780	4.252	72/53
8-80	055408-MNA	M80x2.0	0.787	2.323	2.717	2.560	3.051	5.591	0.016	0.124	3.780	4.252	80/59
9s-90s	055499-MNA	M90x2.0	0.787	2.598	2.953	2.874	3.406	6.142	0.016	0.138	4.370	4.921	89/66
9-90	055409-MNA	M90x2.0	0.787	2.913	3.209	3.227	3.581	6.142	0.016	0.138	4.370	4.921	89/66
10-10	055410-MNA	M100x2.0	0.787	3.189	3.583	3.542	3.935	6.811	0.016	0.138	4.921	5.551	98/72

All dimensions are in inches. Intermediate thread sizes are available on request.

FITTING INSTRUCTION

ENCLOSURES AND EQUIPMENT TO WHICH CABLE GLANDS ARE FITTED:-

- Must be made from materials which are compatible with the cable gland materials.
- Have a sealing area around the cable gland entry point with a surface roughness < Ra 6.3 µm.
- Have entries that are perpendicular to the enclosure face in the area where the cable gland will seal to within 2.5°.
- Are sealed using the supplied sealing gasket (parallel threads) or by fully tightening into a threaded entry (tapered threads). Note that for tapered threads the IP rating can be improved to IP68 with the use of a suitable thread sealant.


MUST HAVE THREADED ENTRIES

- The same thread size as the cable gland. (Thread adapters should be used to correct

- any mismatch).
- With a thread tolerance of metric class '6H' or equivalent.
- Where the thread length is a minimum of 10mm for Ex d applications or 3mm for all other applications


OR CLEARANCE HOLES (not Ex d)

- Where the hole size is the thread nominal size with a tolerance of +0.1 to +0.7mm. (e.g. the clearance hole for an M20 thread will have a diameter between 20.1mm and 20.7mm).
- Through material that is between 1mm and 12mm thick. (Thicker materials can be accommodated using glands with extended entry threads.)



Gland Size	Armour Length	Gland Size	Armour Length	Gland Size	Armour Length	Gland Size	Armour Length
00-16ss	20.0	3s-32s	30.0	6s-63s	45.0	9-90	50.0
00-20ss	20.0	3-32	30.0	6-63	45.0	10-100	60.0
0-20s	20.0	4s-40s	30.0	7s-75s	50.0	11-115	60.0
1-20	25.0	4-40	30.0	7-75	50.0	12-120	60.0
2s-25s	25.0	5s-50s	35.0	8-80	50.0	13-130	60.0
2-25	25.0	5-50	35.0	9s-90s	50.0		


- For accurate sizing, use a CCG Dimension Tape (A) on the inner and outer cable sheath. Cut back the cable outer sheath to expose the armour to a length as per the table above.




If the gland has NPT entry threads fitted to a threaded entry, then IP68 (2m) can be achieved by applying one of the following tested and approved grease types to the thread: - Renolit Lubrene CA700 or LX220 EP2, Renolit LC-WP2 or Moly LX2, or Dow Corning 4 Electrical Compound.

- To maintain IP66/68 ensure the gasket (1) is in place. Screw the inner (2) into the apparatus. Tighten the inner (2) to the installation torque using a CCG Spanner (7).


Alternative installation through an unthreaded entry.




If the apparatus is unthreaded use a locknut.




- Pass the outer nut (4) and the body (3) over the cable.




- Pass the cable end through the inner (2). Splay the armour wires over the cone (5).



- Tighten the body (3) onto the inner (2) until hand tight, then tighten with a CCG Spanner (7) with 3/4 turn to lock the armour between the cone (5) and the cone ring (6).



- Unscrew the body (3). Check that the armour has locked between the cone (5) and cone ring (6). (O-Ring on the cone ring (6) is sacrificial).



- Tighten the body (3) onto the inner (2) to the installation torque using a CCG Spanner (7). The Variable Deluge Seal™ will engage automatically as the body is tightened onto the inner (2). Tighten the outer nut (4) to produce a moisture proof seal by turning until the seal makes contact with the outer sheath of cable and then make one full turn.